

49" Touch Screen Digital Signage Standee

Right message at the right time

JXD DS495PCT



Specifications

JD MOLECULE
beyond outsourcing

PANEL	Panel Type	49" TFT LED	MULTIMEDIA	USB Playback Audio	AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA	
	Lamp Type	WLED		USB Playback Picture	BMP, GIF, JPEG, JPG	
PC SPECIFICATION	Max Resolution	1920 x 1080	USB Playback Video	M2TS, M4V, MK3D, MKV, MP4, MPEG	MPG, MTS, TS, TTS, VOB, WMV	
	Aspect Ratio	16:9 (Portrait / Landscape)	TOUCH	Multi 10 points IR touch		
	Contrast Ratio	1400:1	POWER	Main Power Consumption	AC 100-240V, 50-60Hz	140W
	Brightness	500cd/m2	SOUND	Built-in Speaker	2 x 10W	
	Response Time	8ms	TEMPERATURE	Operating Temperature	0°C to 40°C	
	Display Area	1102 x 638mm		Storage Temperature	-20°C to 60°C	
	Panel Size	1873 x 718 x 65mm	DIMENSION & WEIGHT	Standee Size	1873 x 718 x 65mm	
	CPU	Intel Celeron Quad Core Processor, 2.0 Ghz		Base	718 x 48 x 460mm	
	Chipset	Intel HM76		Standee Weight	98kg	
	BIOS	Intel HD Graphics 4000		Base Weight	12.5kg	
OS	Windows 10 IOT	STRUCTURE	Material	MS Steel Plate Frame		
Memory	4GB RAM, 120GB SSD		Thickness	1.2 - 1.5mm Slim Smart Design		
Audio	Realtek ALC662		Glass	4mm thickness tempered glass		
Ethernet LAN	2 x RTL8111e LAN	FEATURE	Moistureproof, Anti-rust treatment, Anti-dust, Static Free			
CONNECTOR	Rear Panel I/O	HDMI x 1	ACCESSORIES	Castor, User Manual, Keys, Tools & Screws		
		VGA x 1				
		RJ-45 x 1				
		USB 2.0 x 1				
		USB 3.0 x 1				
		Audio I/O (Mic & Line Out)				
CONNECTIVITY	LAN	RJ45 Port, 10/100m Ethernet				
	WiFi	Built-in WiFi 802.11B B/G/N				
	3G (Optional)	WCDMA				

Distributed by



JD Molecule Sdn Bhd | 16B, Jalan Astaka U8/L, Bukit Jelutong, 40150 Shah Alam Selangor | www.jdmolecule.com

Recommended Backend CMS

NAVORI LABS
DIGITAL SIGNAGE ENGINE

Specifications are subject to change without prior notice
Trademarks are the property of their respective owners
Copyright © 2018 All Rights Reserved

Version 1.2